

**SPECIFICATION AMENDMENTS:**

Please replace the paragraph bridging pages 1 and 2 with the following amended paragraph:

--Refer to Fig.1, a conventional baseball glove is composed of a shell back (a), a shell palm (b), both made of leather, a lining and leather lacings. A piece of leather is cut to finger-style pieces for making shell back (a) and a shell palm (b) respectively. The lining includes an inner layer of leather with a soft layer of sponge or soft material. At first, the shell back (a) corresponds the shell palm (b), and sewed together so as to form a glove while an opening is left. The surface of the lining is painted with glue and is attached on the inner side of the glove. The leather lacings are used for binding some leather accessories on the glove for enhancing the strength. In addition, during the sewing process of the shell back (a) and the shell palm (b), a piece of leather gusset (c) is disposed therebetween for increasing the strength of the glove. However, this brings the disadvantage of the hardness of the glove so that it's difficult for users to fold the ~~big toe~~ thumb and other fingers, and is also difficult for catching balls. Moreover, the glove covers users' hand so that the sweat caused by the stifling glove makes users uncomfortable.--

Please replace the paragraph on page 3, lines 1-5 with the following amended paragraph:

--The gusset not only improves the elasticity of the finger part of the glove but also make the glove more foldable, easily receiving the ball. The gusset increase the air permeability so that the heat energy coming from the palm can be dissipated fast, ~~make~~ making users more comfortable.--

Please replace the paragraph bridging pages 4 and 5 with the following amended paragraph:

--Refer to Fig.2 & Fig.3A, the present invention includes a shell back 10, a shell palm 20, a lining 30, a plurality of gussets 40, leather accessories 50 and leather lacings 60. The shell back 10 is in finger-type shape with a plurality of insertion holes 11 on the front side and the peripheral sides of five fingers thereof. The shell palm 20 is also in fingerlike shape with a plurality of insertion holes ~~11-21~~ 11-21 on the front side, the lateral sides of five fingers and the palm thereof. The lining 30 is composed of a lining palm 31 having a soft lining 31a made of sponge or soft material, sewed together with a palm-shaped lining leather 31b, a lining finger 32 made of soft lining 32a located on the position of five fingers, and a plurality of insertion holes 33. The lining 30 is used to increase the thickness of the palm of the glove so as to reduce the injury caused by the impulse of the ball. The insertion holes 33 are for the insertion of the lacings 60 to modify the appearance or increase the strength. The gussets 40 made of special material such as

Neoprene is cut to proper size and is sewed on the position between the two contiguous fingers of the shell back 10. The leather accessories 50 include a web 51 between the thumb and the first finger for receiving balls, an adjustable band 52 for adjusting the fitness of the wrist. The lacings 60 are made by cutting the leather into slips and are inserted through the insertion holes 11, 21, 33 on the lateral side of the glove for beautification and strength enhancement.--